


TDLNA0840EP

Technical
Specifications

0.3-4 GHz UHF Wideband
Ultra Low Power LNA

Power Consumption: 30 mW max.
Gain: 29 dB typical
Noise Figure: 1.5 dB typical @ 25 °C




Product Overview

The TDLNA0840EP is a UHF, wideband, low power LNA MMIC. It provides a typical gain of 29 dB and a typical NF of 1.5 dB across the operating frequency range, with a maximum power consumption of only 30 mW from a 1.5-volt supply. The RF ports are internally dc blocked and matched to 50 ohms. The TDLNA0840EP is packaged in a 3 x 3 x 0.9 mm, 16-lead, plastic over molded QFN.

Typical applications include terrestrial military, avionics, and LEO space applications. It is well suited for phased antenna arrays for communication systems due to its low noise, low power consumption, and flat gain response.

Features

- Frequency Range: 0.3 GHz to 4 GHz
- Power Consumption: 30 mW maximum
- Gain: 29 dB typical
- NF: 1.5 dB typical @ 25 °C
- 3 x 3 x 0.9 mm 16L plastic QFN
- Operating Temperature Range: -55 °C to 125 °C



Absolute Maximum Ratings⁽¹⁾

Parameter	Symbol	Value
Drain Bias Voltage	V _d	4 V
Junction Temperature	T _J	175 °C
Maximum Power Dissipation	P _{diss}	50 mW
Package Theta-JC	θ _{JC}	125 °C/W
RF Input Power (20% duty cycle)	RFin	+28 dBm
Storage Temperature	T _{storage}	-55 to 150 °C

(1) Operation outside these conditions may cause permanent damage to the device. Combination of maximum rating conditions may reduce the values. Device performance at these ratings is not implied.


Electrical Specifications

. V_d = 1.5 V, F_{in} = 0.3 to 4.0 GHz, R_L = 50 Ω, and T_A = -55 °C to +125 °C unless specified otherwise


Parameter	Conditions	Min.	Typ.	Max.	Unit.
Supply Voltage, V _d		0.85	1.5	3	V
Supply Current, I _d		5	15	20	mA
Power Consumption	T _A ≤ 85 °C 85 °C > T _A ≤ 125 °C			25 30	mW mW
Frequency Range		0.3		4	GHz
Small Signal Gain		27	29	32	dB
P1dB Input Power		-37	-35	-30	dBm
Noise Figure	1.0 to 4.0 GHz 0.3 to 4.0 GHz		1.5 2	3.5 5.0	dB dB
I/P Return Loss		5	10		dB
O/P Return Loss		5	10		dB
Stability Factor		1			mu
Operating Temperature		-55		125	°C
ESD	HBM			500	V
	CDM			1000	V

Measured Performance Over Temperature


Small Signal Gain (S21) vs. Frequency




Isolation (S12) vs. Frequency




Input Return Loss (S11) vs. Frequency




Output Return Loss (S22) vs. Frequency




P1dB Input Power vs. Frequency



Noise Figure vs. Frequency



Packaging Marking and Outline Information




SYMBOLS	DIMENSIONS IN MILLIMETERS		
	MIN	NOM	MAX
A	0.80	0.90	1.00
A1	0	0.02	0.05
A3	---	0.25REF.	---
b	0.18	0.23	0.30
D	2.85	3.00	3.15
D1	---	1.8BSC	---
E	2.85	3.00	3.15
E1	---	1.8BSC	---
e	---	0.50BSC	---
L	0.30	0.35	0.45
o	0	---	12
aaa	---	0.25	---
bbb	---	0.10	---
ccc	---	0.10	---
M	---	---	0.05

1. ALL DIMENSIONS ARE IN MILLIMETERS, θ IS IN DEGREES.
2. M: THE MAXIMUM ALLOWABLE CORNER ON THE MOLDED PLASTIC BODY CORNERS.
3. DIMENSION 'D' DOES NOT INCLUDE MOLD PROTRUSIONS OR GATE BURRS. MOLD PROTRUSIONS AND GATE BURRS SHALL NOT EXCEED 0.15mm PER SIDE.
4. DIMENSION 'E' DOES NOT INCLUDE INTERTERMINAL MOLD PROTRUSIONS OR TERMINAL PROTRUSIONS. INTERTERMINAL MOLD PROTRUSIONS AND/OR TERMINAL PROTRUSIONS SHALL NOT EXCEED 0.20mm PER SIDE.
5. DIMENSION 'b' APPLIES TO PLATED TERMINALS. DIMENSION A1 IS PRIMARILY Y TERMINAL PLATING, BUT MAY OR MAY NOT INCLUDE A SMALL PROTRUSION OF TERMINAL BELOW THE BOTTOM SURFACE OF THE PACKAGE.
6. DIE PAD SIZE 2.0X2.0mm HAS 1.8X1.8mm(BSC) EXPOSED PAD SIZE.
7. JEDEC MO-220


Package Pinout

Top View



Pin #	Pin Name	Description
1, 5-8, 12-14, 16	N/C	No Connection
2	GND	Ground
3	RF IN	RF Input
4	GND	Ground
9	GND	Ground
10	RF OUT	RF Input
11	GND	Ground
15	Vd	Supply Voltage
PAD	GND	RF & DC Ground

Recommended PCB Land Pattern



Ordering Information

Order Code	Description/Date	Package	Shipping Method
TDLNA0840EP	0.3 to 4.0 GHz UHF to S-Band LNA	16L, 3 x 3 x 0.9 mm Plastic QFN	Tape & Reel
TDLNA0840-00	Evaluation Board with SMA Connectors	16L, 3 x 3 x 0.9 mm Plastic QFN	Box

Note: If requirements include burn-in, please select the alternative part TDLNA0840SEP which is burned in.

Revision Information

Document	Description/Date	Change/Revision Details
TDLNA0840EP_12_2025 Rev -	TDLNA0840EP December 17, 2025	Initial Release - Product Specification

Document Categories and Specifications

Advance Information

The product is in a formative or design stage. The data sheet contains design target specifications for product development. Specifications and features may change in any manner without notice.

Preliminary Specification

The data sheet contains preliminary data. Additional data may be added at a later date. Teledyne HiRel reserves the right to change specifications at any time without notice in order to supply the best possible product.

Product Specification

The data sheet contains final data. In the event Teledyne HiRel decides to change the specifications, Teledyne HiRel will notify customers of the intended changes by issuing a CNF (Customer Notification Form).

Sales Contact

For additional information, email us at: hirel@teledyne.com or visit our website: www.teledynehirel.com

Disclaimers

The information in this document is believed to be reliable. However, Teledyne HiRel assumes no liability for the use of this information. Use shall be entirely at the user's own risk. No patent rights or licenses to any circuits described in this document are implied or granted to any third party. Teledyne HiRel's products are not designed or intended for use in devices or systems intended for surgical implant, or in other applications intended to support or sustain life, or in any application in which the failure of the Teledyne HiRel product could create a situation in which personal injury or death might occur. Teledyne HiRel assumes no liability for damages, including consequential or incidental damages, arising out of the use of its products in such applications.

Copyright and Trademark

Trademarks are the property of their respective owners. ©2026, Teledyne HiRel. All rights reserved.