

WITHOUT DRIVER ☒ FS

WITH DRIVER ☐ FSD

2898R-SMT

CUSTOMER Catalog

CUSTOMER P/N

DESCRIPTION TINY₁₆ oscillator (SMT Mount), RoHS Compliant

RF SPECIFICATIONS	TUNING RANGE (GHz)	START 6.0[1]	TO 13.0	STOP
POWER OUT (dBm)	+4	MIN		
POWER VARIATION OVER TUNERANGE (dB)	7	MAX		
HARMONICS (dBc)	-12	MAX	☐	
NON-HARMONICS (dBc)	-70	MAX	☐	
TUNING LINEARITY	±20	MHz MAX	OR +/-	% MAX
TEMPERATURE DRIFT (MHz)	±50	☒ MAX	☐ TYP	
HYSTERESIS (MHz)	25	☒ MAX	☐ TYP	
FREQUENCY PUSHING (MHz/V)	2.0	☒ MAX	☐ TYP	
FREQUENCY PULLING - 1.5:1 VSWR (MHz)	2.0	☐ MAX	☐ TYP	
SSB PHASE NOISE (dBc/Hz)	10 KHZ @ -100	☒ MAX	☐ TYP	
	100 KHZ @ -125	☒ MAX	☐ TYP	

DC SPECIFICATIONS

BIAS +5.0	VDC @ 70	mA	☐ MAX	☒ TYP	
n/a	VDC @ n/a	mA	☐ MAX	☐ TYP	
HEATERS n/a	VDC @	mA	☐ MAX	☐ TYP	
					@ 25 ° C STEADY STATE
mA SURGE AT TURN-ON					☒ MAX ☐ TYP

ENVIRONMENTAL SPECIFICATIONS

SCREENING

TEMP RANGE +10 DEG C TO +60 DEG C COMM ☒ MIL ☐ MIL(S) ☐

TUNING COIL

SENSITIVITY (MHz/mA)	12	☒ TYP	%
RESISTANCE (Ohms)	7.5	☐ MAX ☒ TYP	
INDUCTANCE (mH)	17	☐ MAX ☒ TYP	

FM COIL ☒

SENSITIVITY (KHz/mA)	350	☐ TYP	☒ ±15 %
3 dB BANDWIDTH (KHz)	400	☐ MIN	☒ TYP
RESISTANCE (Ohms)	1	☐ MAX	☒ TYP
INDUCTANCE (uH)	1	☐ MAX	☒ TYP

DRIVER

ANALOG ☐

OR

DIGITAL ☐

TUNING VOLTAGE (V) FROM	TO	NO. OF BITS
CIRCUIT POWER	VDC @	mA, MAX
	VDC @	mA, MAX
	VDC @	mA, MAX
		LATCHING

TRANSPARENT ☐ EDGE TRIG ☐ LEVEL TRIG ☐
OUTLINE IN-051544-00

PRODUCT CODE

OTHER SPECS:

(1) Zero current frequency to be 9.500GHz +/- 300MHz

CONTROLLING DOCUMENT

CUSTOMER (SCD NO. IS) X TELEDYNE

ASSIGNED BY MLK

DATE 6/6/2011

REV 1 MLK 10-26-2011